

CWT 1740 Regular

FLATBED APPLICATOR AND WORKTABLE



FACTS

PART NO	CWT1740-00
DESCRIPTION	CWT 1740 Regular
TABLE LENGTH	4000mm (13ft. 1 in.)
TABLE WIDTH	1720mm (5ft. 8in.)
LENGTH OF WORKING AREA	3560mm (11ft. 8in.)
WIDTH OF WORKING AREA/ROLLER WIDTH	1 50mm (5ft. 5in.)
OVERALL WIDTH	1925mm (6ft. 4in.)
MAX. THICKNESS OF SUBSTRATE	70mm (0-2.7in.)
WORK HEIGHT	775-945mm (2ft.6in 3ft.1in.)
WORK HEIGHT ADJUSTMENT*	Manual - 4 steps
BED SURFACE	Safety glass + Cutting mat
POWER SUPPLY**	230V/50Hz (10A) or 120V/60Hz (15A)
REQUIRED AIR SUPPLY	6-8bar (87-116psi)
NET WEIGHT	495kg (1091lbs)
GROSS WEIGHT	650kg (1433lbs)
PACKING DIMENSIONS	4150 x 560 x 2100mm (13ft. 8in. x 1ft. 10in. x 6ft. 11in.
WARRANTY	3 years

FEATURES

ROLL HOLDER FOR GLIDE BEAM	Included
SIDE POCKETS	Included
CASTERS	Included
CWT LIGHT, ILLUMINATED WORKTABLE	Option
CWT LIFT, ELECTRONIC WORK HEIGHT ADJUSTMENT	Option
ROLL HOLDER FOR BED END	Option
PRO SHAFT 1700***	Option
LINEAR CUTTER QUICK DOCK****	Option
SILENT COMPRESSOR	Option
COMPRESSOR SHELF FOR 1700 SERIES	Option
CUTTER BENCH FOR 1700 SERIES****	Option
ROLL CRADLE, ROLL HOLDER FOR TABLE TOP	Option
LOWER ROLL HOLDER	Option

^{*} Select 1 of 4 fixed heights at installation

Only applicable when including CWT Light or CWT Lift.

*** Tensioning shaft with brake and flange guide for the glide beam media holder.

**** Smart brackets for the Linear Cutter, designed to create a trimming station at the short side.

**** A bracket that fits a wide range of cutters and slitters, such as the Inglet

InBest Pro Cutter Bar™, and KeenCut Evolution2 and Evolution3™ SmartFold.